



CECHY PRODUKTU

Kuty. Fosforanowany. Wzmocniona główka do pobijania. Wykonany ze stali chromowo-molibdenowej. DIN 7444* nie dotyczy: 36922, 36924, 36938.



KOD	HRC	ROZMIAR [MM]	L [MM]	D [MM]	T [MM]	G [MM]	
36922	HRC 38 (± 2)	22	160	42	15,5	8	5/50
36924	HRC 38 (± 2)	24	162	42	15,5	8	5/50
36927	HRC 38 (± 2)	27	178	45,5	16,5	9,5	5/50
36930	HRC 38 (± 2)	30	187	51,5	17	9,5	5/50
36932	HRC 38 (± 2)	32	190	51,5	17,5	9,5	5/50
36936	HRC 38 (± 2)	36	203	57	18	10,5	5/40
36938	HRC 38 (± 2)	38	204	57	18	10,5	5/40
36941	HRC 38 (± 2)	41	230	66	21	12	5/20
36946	HRC 38 (± 2)	46	237	73	22	13,5	5/20
36950	HRC 34 (± 2)	50	253	79,5	24,5	15,5	2/12
36955	HRC 34 (± 2)	55	270	88	25,5	16,5	2/12
36960	HRC 34 (± 2)	60	280	93	27,5	18	2/12
36965	HRC 34 (± 2)	65	280	101	28,5	17,5	2/12

PROLINE®



<https://pl-pl.facebook.com/ProlineTools>

www.proline-tools.com