




**SDS
plus**



KOD	ŚREDNICA [MM]	DŁUGOŚĆ CAŁK. [MM]		KOD	ŚREDNICA [MM]	DŁUGOŚĆ CAŁK. [MM]	
80411	4	110	25/250	81045	10	450	25/100
80416	4	160	25/200	81060	10	600	20/40
80511	5	110	25/250	81211	12	110	25/250
80516	5	160	25/200	81216	12	160	25/200
80611	6	110	25/250	81221	12	210	25/100
80616	6	160	25/200	81226	12	260	25/100
80621	6	210	25/100	81230	12	300	25/100
80626	6	260	25/100	81235	12	350	25/100
80811	8	110	25/250	81240	12	400	25/100
80816	8	160	25/200	81245	12	450	25/100
80821	8	210	25/100	81260	12	600	20/40
80826	8	260	25/100	81280	12	800	20/40
80830	8	300	25/100	81316	13	160	25/200
80835	8	350	25/100	81326	13	260	25/100
80840	8	400	25/100	81335	13	450	25/100
80845	8	450	25/100	81416	14	160	25/100
81011	10	110	25/250	81421	14	210	25/100
81016	10	160	25/200	81426	14	260	25/100
81021	10	210	25/100	81430	14	300	25/100
81026	10	260	25/100	81440	14	400	25/100
81030	10	300	25/100	81445	14	450	20/40
81035	10	350	25/100	81460	14	600	20/40
81040	10	400	25/100	81616	16	160	20/80

CECHY PRODUKTU

Ostrze z płytki z węgla spiekane (TCT) z powiększonym wierzchołkiem centrującym pozwala na wwiercanie się bez ześlizgiwania. Szybkie odprowadzenie odwiertnin z otworu. Do wiercenia w betonie niezbrojonym, kamieniu naturalnym, cegle, murze. Dostarczane pojedynczo na zawieszce.



SDS
plus

KOD	ŚREDNICA [MM]	DŁUGOŚĆ CAŁK. [MM]		KOD	ŚREDNICA [MM]	DŁUGOŚĆ CAŁK. [MM]	
81621	16	210	20/80	82221	22	210	10/20
81626	16	260	20/80	82226	22	260	10/20
81630	16	300	20/80	82230	22	300	10/20
81635	16	350	20/40	82240	22	400	10/20
81640	16	400	20/40	82245	22	450	10/20
81645	16	450	20/40	82260	22	600	10/20
81660	16	600	20/40	82280	22	800	10/20
81680	16	800	20/40	82426	24	260	10/20
81821	18	210	10/20	82440	24	400	10/20
81826	18	260	10/20	82460	24	600	10/20
81835	18	850	10/20	82480	24	800	10/20
81840	18	400	10/20	82530	25	300	10/20
81845	18	450	10/20	82545	25	450	10/20
81860	18	600	10/20	82560	25	600	10/20
82021	20	210	10/20	82626	26	260	10/20
82026	20	260	10/20	82640	26	400	10/20
82030	20	300	10/20	82660	26	600	10/20
82040	20	400	10/20	82840	28	400	5/10
82045	20	450	10/20	82860	28	600	5/10
82060	20	600	10/20	82880	28	800	5/10
82080	20	800	10/20				

CECHY PRODUKTU

Ostrze z płytki z węgla spiekane (TCT) z powiększonym wierzchołkiem centrującym pozwala na wwiercanie się bez ześlizgiwania. Szybkie odprowadzenie odwiertnin z otworu. Do wiercenia w betonie niezbrojonym, kamieniu naturalnym, cegle, murze. Dostarczane pojedynczo na zawieszce.